TITLE OF THE INVENTION

PRINTING APPARATUS, PRINTING SYSTEM AND CONTROL METHOD FOR PRINTING APPARATUS

5 ### FIELD OF THE INVENTION

The present invention relates to a printing apparatus, a printing system, a control method of a printing apparatus, and a printer driver, and more particularly, to the control for performing printing by

10 scanning a carriage being capable of mounting an inkjet printhead discharging ink.

BACKGROUND OF THE INVENTION

A printing apparatus capable of printing desired

15 information such as texts and images on a sheet-type printing medium, e.g., paper, film, and the like, is widely utilized as a data output apparatus in a word processor, a personal computer, a facsimile, and so forth.

20 Although various printing methods are available for such printing apparatus, recently an inkjet printing method has particularly attracted the attention because of its capability to perform non-contact printing on a printing medium such as paper,

25 ease of color printing, and low noise. In general, a serial printing method is widely adopted because of its low cost and ease of downsizing. The configuration for

the serial printing method includes a printing unit for reciprocally scanning a carriage incorporating a printhead discharging ink in accordance with desired printing data, and a conveyance unit for conveying a

5   printing medium in a direction orthogonal to the scanning direction.

For improved printing speed, recently there are increasing numbers of printing apparatuses adopting the so-called bi-directional printing, in which printing is

10 performed during the forward and backward scanning of the printing unit.

When printing, discharge timing should be corrected so that ink is discharged at the same position on a printing medium. For example, in a

15 printing apparatus capable of bi-directional printing normally has a function for correcting ink discharge timing of the bi-directional printing so that ink is discharged at the same position on a printing medium in the forward and backward printing. By virtue of this

20 correction function, excellent printing quality is ensured (refer to, e.g., Japanese Patent Application Laid-Open (KOKAI) No. 2001-129985). This document also discloses a typical correction method.

The ink discharge timing correction must

25 mandatorily be performed before bi-directional printing. If the correction is not performed, intrinsic printing quality of the printer cannot be

assured.

However, in reality, the printing apparatus is so constructed that printing is executable regardless of whether or not the ink discharge timing correction is

5 performed for bi-directional printing.

There are some printer drivers which give a warning message to execute the ink discharge timing correction for bi-directional printing, when the printer driver is installed in an external host device.

10 However, since installation of a printer driver is performed independently of the state of a printing apparatus, the warning message does not guarantee execution of the ink discharge timing correction.

15   SUMMARY OF THE INVENTION

The present invention has been proposed in view of the above-described situation. The object of the present invention is to prompt execution of the printing timing correction when printing is performed

20 by a printing apparatus performing printing by scanning a carriage, and to enable printing with intrinsic printing quality of the printing apparatus.

In order to attain the above object, according to one aspect of the present invention, there is provided

25 a printing apparatus for performing printing by scanning a carriage being capable of mounting an inkjet printhead for discharging ink, comprising: correction

means for performing correction of printing timing for adjusting a printing position in the printing; and non-volatile storage means for storing information on whether the correction has been performed or not, which

5   can be obtained when the correction is executed.

In other words, according to an inkjet printing apparatus of the present invention which performs printing by scanning a carriage being capable of mounting an inkjet printhead discharging ink, correction

10   of printing timing is performed for adjusting a printing position in the printing, and information on whether the correction has been performed or not that can be obtained when the correction is executed is stored in non-volatile memory means.

15   By virtue of this configuration, every time a user designates printing in a host device, the host device requests the printing apparatus to transmit information on the correction has been performed or not. If the correction has not been performed, the host device

20   displays a message to the user.

Therefore, it is possible to have a user perform correction of printing timing before the printing. As a result, printing can be performed with intrinsic printing quality of the printing apparatus, in which a

25   deviation of printing positions in the scanning is corrected.

The information may include a correction value

for discharge timing of ink.

In the case where the printing apparatus is adapted to perform printing by bi-directional scanning, the correction means may correct printing timing for

5   scanning in a forward direction and printing timing for scanning in a backward direction.

Note that the present invention is applicable not only to the above-described printing apparatus, but also to a printing system, a control method of a printing

10   apparatus, a printer driver, and a storage medium storing the printer driver.

Other features and advantages of the present invention will be apparent from the following descriptions taken in conjunction with the accompanying

15   drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

20   The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

25   Fig. 1 is a perspective view showing an outer appearance of a printing apparatus according to an embodiment;

- 5 -

Fig. 2 is a view of a printhead cartridge shown in Fig. 1, which is seen from the printing surface of a paper sheet;

Figs. 3A and 3B are explanatory views of an ink discharge state in bi-directional printing, which are seen from the X-Y cross-section in Fig. 1;

Fig. 4 is a block diagram showing an internal construction of an inkjet printing apparatus and a host device;

Fig. 5 is a flowchart describing a process executed when printing is designated in a host device;

Fig. 6 is a perspective view showing an overall construction of an inkjet printer according to an embodiment; and

Fig. 7 is a perspective view showing a state where a battery charger is mounted to the inkjet printer shown in Fig. 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described in detail in accordance with the accompanying drawings.

In the following embodiments, an inkjet printing system, which includes a printing apparatus utilizing an inkjet printing method and a host device for the printing apparatus is explained as an example.

In this specification, "print" is not only to

form significant information such as characters and
graphics, but also to form, e.g., images, figures, and
patterns on printing media in a broad sense, regardless
of whether the information formed is significant or

5   insignificant or whether the information formed is
visualized so that a human can visually perceive it, or
to process printing media.

"Print media" are any media capable of receiving
ink, such as cloth, plastic films, metal plates, glass,

10   ceramics, wood, and leather, as well as paper sheets
used in common printing apparatuses.

Furthermore, "ink" (to be also referred to as a
"liquid" hereinafter) should be broadly interpreted
like the definition of "print" described above. That

15   is, ink is a liquid which is applied onto a printing
medium and thereby can be used to form images, figures,
and patterns, to process the printing medium, or to
process ink (e.g., to solidify or insolubilize a
colorant in ink applied to a printing medium).

20   Fig. 6 is a perspective view showing the overall
arrangement of a printing apparatus according to an
embodiment of the present invention. Fig. 6 shows an
inkjet printer serving as a printing apparatus, a
battery charger serving as a charging device which

25   incorporates a battery and is detachable from the
printer main body, and a cradle serving as a mount for
vertically housing the printer and battery charger

while attaching them. A paper sheet will be
exemplified as a printing medium for printing by the
inkjet printer. The present invention is not limited
to this, and can be applied to any printable sheet-like

5   medium.

In Fig. 6, the outer appearance of an inkjet
printer 800 is an integral shell structure comprised of
an upper case 801, lower case 802, feed cover 803, and
feed port cover 804. The inkjet printer 800 takes this

10   form when it is not used (stands still or is carried).
The side surface of the inkjet printer 800 has a "DC
in" jack (DC power input jack) 817 for inserting an AC
adopter cable serving as a power supply, and an I/F
connector (interface connector) 815 for connecting a

15   USB cable. The feed cover 803 is a printing sheet
supply tray which is opened from the printer main body
to support a printing sheet such as a paper sheet in
printing.

The outer appearance of a battery charger 900 is

20   comprised of a main case 901, cover case 902, and
battery lid 903. The battery lid 903 is detached to
open the main case 901, allowing removing a battery
pack serving as a battery charger.

The mounting surface (connection surface) of the

25   battery charger 900 to the inkjet printer 800 has a
main body connector 904 for electrical connection, and
fixing screws 905 and 906 for mechanical attachment and

- 8 -

fixing. The battery charger 900 is connected to the

printer main body in a direction indicated by an arrow

A in Fig. 6 to drive the printer by the battery. The

top surface of the battery charger 900 has a charge

5   indicator 909 which indicates the charging state of the

battery. The side surface of the battery charger 900

has a "CHG-DC in" jack 907 for inserting an AC adopter

cable serving as a power supply, and a cover plate 908

for covering the "DC in" jack 817 of the inkjet printer

10   800 when the battery charger 900 is attached.

A cradle 950 functions as a mount by inserting it

in a direction indicated by an arrow B in Fig. 6 while

the battery charger 900 is attached to the inkjet

printer 800.

15   Fig. 7 is a perspective view showing a state in

which the battery charger 900 is mounted on the inkjet

printer 800 when the printer back surface and printer

top surface are viewed diagonally from the top.

As shown in Fig. 7, the battery charger 900 is

20   attached to the back surface of the inkjet printer 800,

and fixed with the fixing screws 905 and 906 to

implement a battery-driven printer.

As described above, the "DC in" jack 817 of the

inkjet printer 800 is covered with the cover plate 908

25   of the battery charger 900. In attaching the battery

charger 900, the user reliably inserts the AC adopter

cable to the "CHG-DC in" jack 907 of the battery

charger 900, thus preventing erroneous insertion.

The back surface of the battery charger 900 has four legs 901a, 901b, 901c, and 901d on the main case 901. This back surface also has contacts 910a, 910b,

5   and 910c for electrical contact upon attachment to the cradle 950.

As shown in Fig. 7, the charge indicator 909 of the battery charger 900 is arranged at a position where, even when the feed cover 803 is opened, the feed

10   cover 803 does not interrupt visual recognition on the top surface on which the charge indicator 909 can be easily visually recognized in mounting or using the inkjet printer 800.

Fig. 1 is a perspective view showing an outer

15   appearance of an inkjet printing apparatus. An inkjet printing apparatus 800 performs a printing operation by driving various mechanical parts shown in the drawing. A paper sheet 102 serving as a printing medium is inserted to the printer main body by a pickup roller

20   103, conveyed to a predetermined paper-feed position, then conveyed to a predetermined printing position inside the printer by a conveyance roller 104 to be subjected to a printing operation, and outputted by a discharge roller 105.

25   While the paper sheet 102 is conveyed, a carriage 106 incorporating a printhead cartridge 110 serving as a printing unit of the printer is driven by a carriage

driving belt 108 which transmits power from a carriage

driving motor 107, to scan over the paper sheet. In

synchronization with the carriage motion, a driving

signal and a control signal are transmitted from a

5   flexible cable 109 to the printhead cartridge 110. In

accordance with the signals, ink supplied from an ink

tank 111 is discharged to the paper sheet 102, thereby

performing printing.

      While paper feeding operation is performed by

10   rotating the pickup roller 103, a sensor 112 which

detects a paper edge determines existence or absence of

a paper sheet. By the detection of the sensor 112, the

internal position of the paper sheet is also

controlled. The paper sheet, conveyed to the

15   predetermined printing position by the conveyance

roller 104, is conveyed also by the driving force of

the discharge roller 105.

      Fig. 2 is a view of the printhead cartridge 110

shown in Fig. 1, which is seen from the printing

20   surface of the paper sheet.

      The printhead cartridge 110 comprises a nozzle

unit 202 for discharging ink. The nozzle unit 202 has

discharge orifices 203 for discharging yellow (Y),

magenta (M), cyan (C), and black (B) inks respectively.

25   The ink of respective colors is discharged from the

orifices to the paper sheet, thereby forming a desired

image. In other words, each of the nozzles discharging

ink serves as a printing element.

For an ink discharging method, a method utilizing heat energy, a method utilizing a piezoelectric device, and the like are known. Any of these methods may be

5   adopted.

Figs. 3A and 3B are explanatory views of an ink discharge state seen from the X-Y cross-section in Fig. 1, when bi-directional printing is performed according to this embodiment.

10   Fig. 3A shows a case where the printhead cartridge 110 is scanned from X to Y in the forward direction. Fig. 3B shows a case where the printhead cartridge 110 is scanned from Y to X in the backward direction. The line X-Y in Figs. 3A and 3B indicates

15   the printing surface.

When the printhead cartridge 110 is scanned at predetermined speed, ink discharged from the discharge nozzle unit 202 has a velocity vector 302 or 304, which is the composition of the discharge speed toward the

20   printing surface and the speed toward the scanning direction. To land ink at the desired landing position 301, in the case of the forward scanning shown in Fig. 3A, it is necessary to discharge ink when the nozzle unit 202 facing the printing surface is at the position

25   303 in the scanning direction. In the case of the backward scanning shown in Fig. 3B, it is necessary to discharge ink when the nozzle unit 202 facing the

printing surface is at the position 305 in the scanning direction.

As described above, when bi-directional printing is performed, there is a difference, represented by the distance 306, in the ink discharge position between forward scanning and backward scanning. To perform high-quality printing, it is necessary to calculate the distance 306 as a correction value and correct the ink discharge timing in the forward path and backward path.

Note that the correction method of ink discharge timing is not limited to a particular method in this embodiment. For instance, a method proposed by the aforementioned document (Japanese Patent Application Laid-Open (KOKAI) No. 2001-129985) may be employed.

Fig. 4 is a block diagram showing an internal construction of the inkjet printing apparatus and a host device according to this embodiment.

An inkjet printing apparatus 401 performs data reception through an I/F unit 402 which inputs or outputs data from or to an external unit, an I/F control unit 403 which controls the I/F unit 402, and a reception data storage area 404 which stores data received through the I/F unit. A control unit 405, which controls the entire apparatus, generates printing data based on the data stored in the reception data storage area 404, and the generated printing data is stored in a printing data storage area 407. Also, the

control unit 405 controls a paper conveyance device 408

and a printing device 409 including a printhead to

execute printing on a paper sheet.

When the inkjet printing apparatus performs

5   correction of ink discharge timing, it also stores

information indicating that correction has been

performed as well as the correction value of ink

discharge timing in the non-volatile storage area 406.

Although this embodiment gives as an example the

10   information indicating that the correction has been

performed, the information may be of data indicative of

the state of correction, or may be of information

indicating that correction has not been performed. In

this case, the control is changed accordingly.

15   Meanwhile in a host device 410, a printer driver

for the inkjet printing apparatus 401 is installed.

When a printing operation is designated by an

application program, the printer driver executes the

process which will be described later to perform

20   printing. More specifically, printing data is

generated by a data generation control unit 411, the

generated printing data is temporarily stored in a

spool area 412 and transmitted to the inkjet printing

apparatus 401 through an I/F unit 413. Information

25   from the inkjet printing apparatus 401 is transmitted

from the I/F unit 402 to the I/F unit 413 of the host

device. information or warning for a user is displayed

on a display unit 414 by the data generation control
unit 411.

The connection between the inkjet printing
apparatus 401 and the host device 410 may be realized
5   with wires or without wires, as long as data
transmission/reception is realized between the I/F
units of these apparatuses.

Fig. 5 is a flowchart describing a process
executed by the printer driver when printing is
10 designated in the host device according to the present
embodiment.

When printing is designated by an application
program operating in the host device, the printer
driver first requests the inkjet printing apparatus to
15 transmit information related to the correction of ink
discharge timing (a correction value of ink discharge
timing and information indicative of whether or not
correction has been performed) (step S501). Then it is
determined whether or not the printer driver has
20 received the information from the printing apparatus
(step S502). If the information has not been received,
it is determined whether or not a predetermined time-
out duration has elapsed (step S503). If the time-out
duration has not elapsed, the control returns to step
25 S502. If the time-out duration has elapsed, printing
is executed regardless of whether or not the
information has been received from the printing

apparatus (step S504).

If it is determined in step S502 that the printer driver has received the information from the printing apparatus, it is determined whether or not ink

5   discharge timing correction has been performed (step S505). If ink discharge timing correction has already been performed, printing is executed immediately (step S504). Meanwhile, if it is determined that ink discharge timing correction has not been performed, a

10 message is displayed by the display unit to warn the user that ink discharge timing correction has not been performed and request execution of the correction (step S506).

In this case, the printer driver holds the

15 standby state until the user designates execution of the ink discharge timing correction (step S507). When execution of the ink discharge timing correction is designated by the user, the ink discharge timing correction is executed (step S508). To reflect the

20 result of ink discharge timing correction (correction value) on printing, the control returns to step S501, and information related to the ink discharge timing correction is requested to the printing apparatus.

As described above, according to this embodiment,

25 every time a user designates printing, the printing apparatus is requested to transmit information related to ink discharge timing correction. If the correction

- 16 -

has not been performed, execution of ink discharge
timing correction is requested.

Accordingly, it is possible to have a user
perform ink discharge timing correction before bi-
5   directional printing. As a result, printing can be
performed with intrinsic printing quality of the
printing apparatus, in which a deviation of printing
positions in the forward and backward scanning of the
bi-directional printing is corrected.
10 <Modified Embodiment>

The above embodiment assumes that an inkjet
printing apparatus always performs bi-directional
printing. In a case where a printing apparatus
includes a printing mode for one-directional printing
15 and a printing mode for bi-directional printing, the
process shown in the flowchart in Fig. 5 is performed
only when the printing mode for bi-directional printing
is set.

In the above embodiment, the information related
20 to ink discharge timing correction is used to determine
whether or not correction has been performed and to
obtain a correction value of ink discharge timing.
Alternatively, for instance, an unrealistic correction
value may be set as an initial value in the printing
25 apparatus to indicate that ink discharge timing
correction has not been performed yet. In this case,
the information related to ink discharge timing

- 17 -

correction only includes a correction value of ink
discharge timing.

<Other Embodiments>

The present invention can be applied to a system

5   comprising a plurality of devices or to an apparatus
comprising a single device.

Furthermore, the invention can be implemented by
supplying a software program, which implements the
functions of the foregoing embodiments (such as a

10   printer driver corresponding to the flow-chart shown in
FIG. 5), directly or indirectly to a system or
apparatus, reading the supplied program code with a
computer of the system or apparatus, and then executing
the program code. In this case, so long as the system

15   or apparatus has the functions of the program, the mode
of implementation need not rely upon a program.

Accordingly, since the functions of the present
invention are implemented by computer, the program code
installed in the computer also implements the present

20   invention. In other words, the claims of the present
invention also cover a computer program for the purpose
of implementing the functions of the present invention.

In this case, so long as the system or apparatus
has the functions of the program, the program may be

25   executed in any form, such as an object code, a program
executed by an interpreter, or scrip data supplied to
an operating system.

Example of storage media that can be used for
supplying the program are a floppy disk, a hard disk,
an optical disk, a magneto-optical disk, a CD-ROM, a
CD-R, a CD-RW, a magnetic tape, a non-volatile type
5   memory card, a ROM, and a DVD (DVD-ROM and a DVD-R).

As for the method of supplying the program, a
client computer can be connected to a website on the
Internet using a browser of the client computer, and
the computer program of the present invention or an
10   automatically-installable compressed file of the
program can be downloaded to a recording medium such as
a hard disk. Further, the program of the present
invention can be supplied by dividing the program code
constituting the program into a plurality of files and
15   downloading the files from different websites. In
other words, a WWW (World Wide Web) server that
downloads, to multiple users, the program files that
implement the functions of the present invention by
computer is also covered by the claims of the present
20   invention.

It is also possible to encrypt and store the
program of the present invention on a storage medium
such as a CD-ROM, distribute the storage medium to
users, allow users who meet certain requirements to
25   download decryption key information from a website via
the Internet, and allow these users to decrypt the
encrypted program by using the key information, whereby

the program is installed in the user computer.

Besides the cases where the aforementioned functions according to the embodiments are implemented by executing the read program by computer, an operating

5   system or the like running on the computer may perform all or a part of the actual processing so that the functions of the foregoing embodiments can be implemented by this processing.

Furthermore, after the program read from the

10 storage medium is written to a function expansion board inserted into the computer or to a memory provided in a function expansion unit connected to the computer, a CPU or the like mounted on the function expansion board or function expansion unit performs all or a part of

15 the actual processing so that the functions of the foregoing embodiments can be implemented by this processing.

If the present invention is realized as a storage medium, program codes corresponding to the above

20 mentioned flowcharts (FIG. 1 and/or FIG. 2) are to be stored in the storage medium.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be

25 understood that the invention is not limited to the specific embodiments thereof except as defined in the

appended claims.